

► NUOVA SIMONELLI

APPRIA II



PRODUCT INFO

The Appria 11 offers enduring Italian design, high-performance technology and super reliability for locations with smaller volume output and minimal counter space, such as restaurants and small coffee shops. Available in 1-3 group.

KEY FEATURES

- Utilising the copper boiler, the heat exchanger allows you to brew & steam simultaneously at a fast rate
- SIS — Soft Infusion System guarantees velvety coffee every time (and compensates for incorrect coffee tamping)
- Automatic Dosing — programmable buttons make it simple to precisely measure the espresso volume
- Hot water economiser for that perfect tea/ long black temperature (not available on single group machines)
- Raised group heads for tall cups
- Reverse mirror offers barista full view of the dispensers without having to bend down
- Highly ergonomic, practical push/pull steam levers & wear-resistant buttons

APPRIA II G1

APPRIA II G2

APPRIA II COMPACT G2

APPRIA II G3



	APPRIA II G1	APPRIA II G2	APPRIA II COMPACT G2	APPRIA II G3
PRODUCT CODE	11006	11007	11078	11008
POWER CONSUMPTION	8.7 Amps / 2000 Watts	19.5 Amps / 4500 Watts	12.1 Amps / 2800 Watts	23 Amps / 5000 watts
BOILER	Copper	Copper	Copper	Copper
MILK FROTHER	Steam Arm	Steam Arm	Manual or Auto Steam	Steam Arm
HOT WATER OUTLET	Yes	Yes	Yes	Yes
WATER REQUIREMENTS	15 mm male outlet tap (within one metre of the machine) below the bench	15 mm male outlet tap (within one metre of the machine) below the bench	15 mm male outlet tap (within one metre of the machine) below the bench	15 mm male outlet tap (within one metre of the machine) below the bench
WEIGHT	42 kg	63 kg	45 kg	80 kg
DIMENSIONS (WDXH)	400 mm x 545 mm x 530 mm	780 mm x 545 mm x 530 mm	550 mm x 545mm x 530mm	1010 mm x 545 mm x 530 mm
POWER	10 Amp single phase HPM	20 Amp single phase HPM	15 Amp single phase HPM	25 Amp Single Phase HPM
DRAINAGE	Either in to S bend or Trap	Either in to S bend or Trap	Either into S trap or bend	Either in to S bend or Trap